



## IN•TEC RELINING SYSTEM IS RENEWED SPRAY COAT IS BORN IN THREE VERSIONS:

*maxi – midi – mini*



- EASY TO MANEUVER FOR OPERATIONS IN RESTRICTED AREA BECAUSE OF ITS LIGHT WEIGHT AND SMALL DIMENSIONS
- FULL AUTOMATIC OPERATION CONTROLLED BY LAST GENERATION SOFTWARE
- STRUCTURAL AND RAPID CURING EPOXY RESIN

**EXCELLENT PRICE/QUALITY RATIO**

SPRAYING MACHINE FOR NO-DIG COATING OF PLUVIAL, BLACK WATER ,BATHROOMS DRAINS AND LATERAL CONNECTIONS USING A TIXOTROPIC AND STRUCTURAL EPOXY RESIN.

CAN COAT PIPES STARTING FROM DN 40MM UP TO 200MM, ALSO WITH BENDS AND CHANGES OF SECTION



### SPRAY COAT *maxi*

Dimensions: 420x330x1120

Weight: 54 kg

Voltage: 220V

Cylinders capacity: A 5,35 lt B 4,30 lt

Cables lengths: up to 17 mt

Resin curing time at 20° C:

UNITEC 120s                      70 minutes

UNITEC 130sr                    25 minutes



### SPRAY COAT *midi*

Dimensions: 320x520x1140

Weight: 35 kg

Voltage: 220V

Cylinders capacity: A 2,70 lt B 2,20 lt

Cables lengths: up to a 9 mt

Resin curing time at 20° C:

UNITEC 120s                      70 minutes

UNITEC 130sr                    25 minutes



### SPRAY COAT *mini*

Dimensions: 330x400x870

Weight: 23 kg

Voltage: 220V

Cylinders capacity: A 1,55 lt B 0,85 lt

Cables lengths: up to 4 mt

Resin curing time at 20° C:

UNITEC 130sr                    25 minutes



IN•TEC S.r.l. Via Torricelli,10 – 20090 Segrate (MI) Italy Tel: +39 02 2692 1865 Fax: +39 02 2692 18  
 P.I./C.F. 10600010150 – Trib. MI 324614/8075/14 – CCIAA MI1389322 – Capitale Sociale € 65.000 i.v.  
[www.intec.biz](http://www.intec.biz)    [info@intec.biz](mailto:info@intec.biz)    [intecsr@pec.it](mailto:intecsr@pec.it)

